

## LINEAR MOTOR

## BACKGROUND OF THE INVENTION

5      Field of the Invention

The present invention relates to a linear motor, and more particularly, to a linear motor having a plurality of permanent magnets assembled with a shaft which is moved rotatably and linearly.

10

Description of the Background Art

~~Figure 1 is a sectional view of a linear motor in accordance with a conventional art, and Figure 2 illustrates arrangement of permanent magnets of the linear motor of Figure 1 in accordance with the conventional art.~~

Generally, as shown in the drawings, a linear motor includes a stator 1 and a rotor 2.

~~The stator 1 includes an outer case 1a, a first armature coil part 1b installed inner side of the outer case 1a, a second armature coil part 1c installed at one side of a support member 1d.~~

~~The rotor 2 includes a shaft 2b and permanent magnets 2a arranged in a checked pattern at an outer~~

TOP SECRET 09761503 011804

Ins a1 →

Ins a2 →

~~circumferential surface of the shaft 2b~~

*Ins.  
a2  
cont.*

~~The first armature coil part 1b is wound in an~~  
annular type at the inner side of the stator 1, and the  
second armature coil part 1c is also wound in the same  
5 annular type as that of the first armature coil part 1b  
at the inner side of the stator 1 but arranged in a  
checked pattern in a perpendicular direction to the  
first armature coil part 1b.

The first armature coil part 1b is linearly moved,  
10 while the second armature coil part 1c assembled in the  
direction perpendicular to the first armature coil parts  
1b is rotatably moved. And, the first armature coil part  
1b and the second armature coil part 1c are formed of  
three-phase (U, V, W, U', V', W') coils.

15 However, in the case that the first and the second  
armature coil parts 1b and 1c adopt the three phases, in  
the conventional linear motor, the plurality of  
permanent magnets corresponding to the first armature  
coil part, that is, the linear movement portion, and the  
20 second armature coil part, that is, the rotation  
movement portion, are arranged and assembled in a  
checked pattern on the outer circumferential surface of  
a single shaft. Thus, when the shaft is linearly moved,  
~~it is difficult to precisely control the shaft due to~~

09761592-011301

*Ins.  
a2  
cancel.*

~~the permanent magnets in the checked pattern in addition, since assembling the permanent magnets in the checked pattern is very difficult, its operation efficiency is degraded.~~

5

# SUMMARY OF THE INVENTION

*Ins.  
a3*

~~Therefore, an object of the present invention is~~  
to provide a linear motor in which a plurality of  
10 permanent magnets arranged and assembled on the outer  
circumferential surface of a shaft are divided into a  
first permanent magnet part, a linear movement zone, and  
a second permanent magnet part, a rotation movement zone,  
in a manner of being corresponded to a first armature  
15 coil part and a second armature coil part as divided  
into a rotation movement zone and a linear movement zone,  
to thereby precisely control linear movement thereof

To achieve these and other advantages and in  
accordance with the purpose of the present invention, as  
20 embodied and broadly described herein, there is provided  
a linear motor including: an outer case; a stator  
installed at the inner side the outer case and having a  
first and a second armature coil parts; a first to a  
~~third shafts assembled in the inner side of the first~~

*Ins.  
a3  
mcd.*

~~and the second armature coil parts of the stator; a first permanent magnet part having a plurality of permanent magnets assembled in a ring-type at the outer circumferential surface of the first shaft; and a second~~  
 5 ~~permanent magnet part having a plurality of permanent magnets assembled at the outer circumferential surface of the third shaft.~~

The foregoing and other objects, features, aspects and advantages of the present invention will become more  
 10 apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention  
 20 and together with the description serve to explain the principles of the invention.

In the drawings:

*Ins.  
a4*

~~Figure 1 is a sectional view of a linear motor in accordance with a conventional art;~~

09761593.011804

Figure 2 illustrates arrangement of permanent magnets of the linear motor of Figure 1 in accordance with the conventional art;

Figure 3 is a sectional view of a linear motor in accordance with the present invention;

Figure 4A is a perspective view of a stator of the linear motor of Figure 3 in accordance with the present invention;

Figure 4B is a perspective view of a rotor of the linear motor of Figure 3 in accordance with the present invention;

Figure 5A is a side-sectional view of the stator of the linear motor of Figure 3 in accordance with the present invention; and

Figure 5B is a side-sectional view of the rotor of the linear motor of Figure 3 in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

~~Figure 3 is a sectional view of a linear motor in~~

09764592-01101  
FOI b7D b7C b7E b7F b7G b7H b7I b7J b7K b7L b7M b7N b7O b7P b7Q b7R b7S b7T b7U b7V b7W b7X b7Y b7Z

Ins.  
a5

*Ins.  
a5  
cancel.*

~~accordance with the present invention, Figure 4A is a perspective view of a stator of the linear motor of Figure 3 in accordance with the present invention, Figure 4B is a perspective view of a rotor of the linear motor of Figure 3 in accordance with the present invention, Figure 5A is a side-sectional view of the stator of the linear motor of Figure 3 in accordance with the present invention, and Figure 5B is a side-sectional view of the rotor of the linear motor of Figure 3 in accordance with the present invention.~~

As shown in Figure 3, a linear motor of the present invention includes a stator 10 and a rotor 20.

With reference to Figures 3 and 4A, the stator 10 includes a first armature coil part 12 disposed at one side of an outer case 11 and a second armature coil part 13 disposed at a predetermined distance from the first armature coil part 12.

*Ins.  
a6*

~~The first armature coil part 12 and the second armature coil part 13 are formed in a similar structure to that of the armature coil parts of the conventional linear motor.~~

Namely, the first armature coil part 12 is disposed in the annular type to fit the outer case 11, and the second armature coil part 13 is assembled in the

09761593-011801

*Ins. Age amended.*

~~outer case 11 in the perpendicular direction to the~~  
first armature coil part 12. A reference numeral 14 of  
Figure 3 denotes a support member.

With reference to Figures 3 and 4B, the rotor 20  
5 includes a first through a third shafts 21, 22 and 23  
insertedly disposed in the outer case 11, a first  
permanent magnet 21a disposed in a ring type on the  
outer circumferential surface of the first shaft 21 and  
a second permanent magnet 23a disposed on the outer  
10 ~~circumferential surface of the third shaft 23.~~

The first and the second permanent magnet 21a and  
23a are positioned to be corresponded to the first and  
the second armature coil parts 12 and 13, respectively.

*Ins. a7*

~~The reason why the rotor is sectioned into the~~  
15 first through the third shafts 21, 22 and 23 is to  
indicate a linear movement zone, a neutral zone, and a  
rotation movement zone.

As shown in Figures 4B and 5A, N pole, S pole, N  
pole and S pole of the first permanent magnet 21a are  
20 arranged in a ring type on the outer circumferential  
surface of the first shaft 21 in the horizontal  
~~direction in the linear movement zone.~~

The N pole, S pole, N pole and S pole of the  
second permanent magnet 23a are arranged on the outer

09764592-011810

circumferential surface of the third shaft 23 in the vertical direction in the rotation movement zone.

*Ins-1  
a8  
cont.*

~~There is formed the neutral zone between the first~~  
 permanent magnet 21a and the second permanent magnet 23a,  
 5 having a predetermined interval therebetween. The  
 neutral zone corresponds to the second shaft 22 as shown  
 in Figure 4B.

As to the linear motor of the present invention constructed as described above, since the rotor 20 is  
 10 formed to be coaxial with the first through the third  
 shafts 21, 22 and 23, its precision can be drastically  
 improved compared with that of the conventional linear  
 motor.

In other words, in case of the conventional linear  
 15 motor, the shaft for the linear movement zone and the  
 shaft for the rotation movement zone are junctioned for  
 use, but comparatively, in case of the linear motor of  
 the present invention, the plurality of permanent  
 magnets formed on the outer circumferential surface of  
 20 the shaft are divided into the first permanent magnet  
 21a, the linear movement zone, and the second permanent  
 magnet 23a, the rotation movement zone, and the first  
 permanent magnet 21a is formed in a ring type to be  
 assembled, so that controlling of the linear movement of

FOR "CONFIDENTIAL"



*Ins.  
as  
mcd.*

~~the linear motor, which is moved rotatably and linearly,~~  
can be improved. In addition, the permanent magnet to be  
assembled in the rotation movement zone of the shaft can  
~~be attached later.~~

5 As so far described, according to the linear motor  
of the present invention, the first permanent magnet and  
the second permanent magnet are separately constructed  
on the outer circumferential surface of the shaft to be  
assembled, so that the linear movement of the linear  
10 motor can be precisely controlled when the linear motor  
is linearly moved, and the permanent magnet to be  
assembled at the rotation movement zone can be attached  
later.

As the present invention may be embodied in  
15 several forms without departing from the spirit or  
essential characteristics thereof, it should also be  
understood that the above-described embodiments are not  
limited by any of the details of the foregoing  
description, unless otherwise specified, but rather  
20 should be construed broadly within its spirit and scope  
as defined in the appended claims, and therefore all  
changes and modifications that fall within the meets and  
bounds of the claims, or equivalence of such meets and  
bounds are therefore intended to be embraced by the

05761593 011301

appended claims.

09764593 011804  
FOOTNOTES